

HIGH FLOW CSR TWIN - 7CLM+ SYSTEM

Part Number: EV977132



SYSTEM DESCRIPTION

Engineered for performance and dependability, the **Everpure High Flow CSR Twin - 7CLM+** water filtration system delivers exceptional water quality for multiple foodservice applications. Its exclusive filtration design reduces chloramines, chlorine, and tastes & odors. The prefilter reduces particulates to 5 microns while the post filter allows scale inhibition. At a flow rate of 3.34 gpm, this system treats up to 16,000 gallons of water for reducing chloramines and chlorine.

FEATURES • BENEFITS

- ◆ High-performance catalytic carbon block technology is engineered to reduce chloramines, chlorine, and tastes & odors and filters sediment as small as 5 microns
- ◆ Manifold features water shut-off, flushing valve, inlet and outlet pressure gauges
- ◆ Easy, quick-change filter replacement
- ◆ SR-X with SS-IMF cartridge inhibits scale buildup in ice machines and coffee brewers*
- ◆ NSF/ANSI Standard 42 certified for the reduction of Chloramines, Chlorine, and Tastes & Odors, and Particulate Class III
- ◆ NSF certified to ASSE 1087

APPLICATIONS

- ◆ Fountain beverage
- ◆ Coffee
- ◆ Ice machines
- ◆ Multiple equipment systems


INSTALLATION TIPS

- ◆ Choose a mounting location suitable to support the weight of the system while operating.
- ◆ Install vertically and allow 2½" (6.35 cm) clearance below the cartridge for easy removal and replacement.
- ◆ Feed water temperature must not exceed 100°F (38°C).
- ◆ Do not install where the system could be exposed to freezing temperatures.
- ◆ Feed water supply pressure must not exceed 125 psi (non-shock). When pressure exceeds 85 psi, a pressure reducing valve is recommended.
- ◆ Flush cartridges by running water through the system for five (5) minutes.
- ◆ For more details, see the installation, operation, and maintenance guide included with the system.

* As tested by Pentair.

HIGH FLOW CSR TWIN - 7CLM⁺

EV977132



SPECIFICATIONS

System	Performance
Overall Dimensions 25.37" L x 25.5" W x 6.96" D (64.44 x 64.77 x 17.68 cm)	Service Flow Rate 3.34 gpm (12.64 Lpm)
Connections Inlet: 3/4" FNPT Outlet: 3/4" FNPT	Rated Capacity Chloramines 16,000 gallons (60,566.59 L) 30,000 gallons (113,562.35 L)*
Operating Pressure 10 – 125 psi (0.7 – 8.6 bar)	Rated Capacity Chlorine 16,000 gallons (60,566.59 L) 30,000 gallons (113,562.35 L)*
Water Temperature 35 – 100°F (2 – 38°C)	Chloramines Reduction Yes
Operating Weight 62.4 lbs (28.3 kgs)	Chlorine Reduction Yes
Shipping Weight 26.66 lbs (12.1 kgs)	Tastes & Odors Reduction Yes
Electrical Connection None required	Particulate Reduction Yes

*As tested by Pentair at a flow rate of 2 gpm (7.57 Lpm).

For Pentair Everpure Product Warranties visit:
<http://pentair.com/assets/foodservice-warranty>.
To receive a free copy email or call your Pentair representative using the information provided below.

Replace all filter cartridges every six (6) months as part of a regular scheduled program and no less than once per year. In multiple-cartridge systems, all primary quick-change cartridges must be replaced simultaneously.

The substances reduced by this drinking water device are not necessarily in your water.

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

REPLACEMENT CARTRIDGE

Model	Qty	Description	Part No
7CLM ⁺	2	Primary filter	EV977100 (1pk)
EC210	1	Prefilter	EV953426 (6pk) EV953420 (20pk)
SS-IMF	1	Scale stick	EV979932 (12pk)



System Tested and Certified by NSF International against ASSE / ANSI 1087 and NSF/ANSI Standard 42 for the reduction of:

STANDARD NO. 42 – AESTHETIC EFFECTS

Chemical Reduction

Taste & Odor

Chloramines

Chlorine

Mechanical Filtration

Nominal Particulate Class III



1040 Muirfield Drive | Hanover Park, IL 60133 | 800.942.1153 (US Only) 630.307.3000 Main | cseverpure@pentair.com | foodservice.pentair.com

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners.

©2026 Pentair. All rights reserved.

EV977132 JL26