

SUBMERSIBLE SOLIDS HANDLING PUMPS

MNG3SC(X), MNG4SC(X), MNG4HC(X), MNG6MC(X) SERIES

PHYSICAL DATA

DISCHARGE SIZE (125 # ANSI FLANGE HORIZONTAL ORIENTATION)	MNG3SC: 3", MNG4SC: 4", MNG4HC: 4", MNG6MC: 6"
IMPELLER TYPE	BALANCED, SEMI-OPEN
CABLE LENGTH	35' STANDARD, 50', 75', 100' OPTIONAL
PAINT	PAINTED AFTER ASSEMBLY. DARK GREEN, WATER REDUCIBLE ENAMEL, ONE COAT, AIR DRIED.

TEMPERATURE

MAXIMUM LIQUID	104° F LABELED/140° F UNLABELED
MAXIMUM STATOR	356° F (180° C)
OIL FLASH POINT	309° F
HEAT SENSOR OPEN	275° F MAX./257° F MIN.
HEAT SENSOR CLOSED	204° F MAX.

TECHNICAL DATA

MOTOR		PREMIUM EFFICIENT, IEC 60034 -30 LEVEL IE3 *			
POWER CORD TYPE		W OR SOOW, WATER RESISTANT, 600V, 90° C			
SENER CORD TYPE		SOOW, 18-5, WATER RESISTANT, 600V, 90° C, 5.5 AMPS			
MATERIALS OF CONSTRUCTION	MOTOR HOUSING	CAST IRON	ASTM	A-48	CLASS 30
	CASING	DUCTILE IRON	ASTM	A-536	CLASS 65
	IMPELLER	440 SST	ASTM	A-276	57-60 HRC
	CHOPPER LINER				
	MOTOR SHAFT	416 STAINLESS STEEL			
	HARDWARE	300 SERIES STAINLESS STEEL			
	O-RINGS	NITRILE			
MECHANICAL STANDARD SEALS		UPPER - C/SIC TYPE 2100, LOWER - C/SIC TYPE 2			
UPPER BEARING		(RADIAL) SINGLE ROW - BALL			
LOWER BEARING		(THRUST) DOUBLE ROW, ANGULAR CONTACT - BALL			

*208V versions will not conform to IE3 standards.

1101 Myers Parkway
Ashland, OH 44805
Ph: 855.274.8947
Fx: 800.426.9446

490 Pinebush Rd., Unit 4
Cambridge, Ontario N1T 0A5, Canada
Ph: 800.363.7867
Fx: 888.606.5484

pentair.com/myers